

DS-KV6133-ME1 IP Villa door station











- 2 MP camera with IR supplement
- One button calling design for easier calls
- Built-in card reader module
- Standard PoE power supply
- IP65 protection level with aluminum alloy casing
- Call directly to Hik-Connect APP without indoor station



SpecificationSystem parameters

Comparison System Comparison	
RAM 256 MB Processor Embeded high performance processor Display parameters Screen size / Operation method / Type / Resolution / Video parameters Lens 1 Resolution Main stream: 1920 × 1080p, 1280 × 720p Sub stream: 1280 × 720p, 640 × 480p FOV Horizontal: 129°, Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Processor Embeded high performance processor Display parameters Screen size / Operation method / Type / Resolution // Video parameters Lens 1 Resolution	
Screen size / Operation method / Type / Resolution / Video parameters Lens 1 Resolution	
Screen size / Operation method / Type / Resolution / Video parameters Lens 1 Resolution Sub stream: 1920 × 1080p, 1280 × 720p Sub stream: 1280 × 720p, 640 x 480p FOV Horizontal:129°, Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Operation method // Type // Resolution // Video parameters Lens 1 Resolution Sub stream: 1920 × 1080p, 1280 × 720p Sub stream: 1280 × 720p, 640 × 480p FOV Horizontal:129°, Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Type // Resolution // Video parameters Lens 1 Resolution Sub stream: 1920 × 1080p, 1280 × 720p Sub stream: 1280 × 720p, 640 x 480p FOV Horizontal:129°, Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Resolution / Video parameters Lens 1 Resolution Sub stream: 1920 × 1080p, 1280 × 720p Sub stream: 1280 × 720p, 640 × 480p FOV Horizontal:129°, Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726 、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Video parameters Lens 1 Resolution	
Lens 1 Resolution Sub stream: 1920 × 1080p, 1280 × 720p Sub stream: 1280 × 720p, 640 × 480p FOV Horizontal:129°, Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Resolution Main stream: 1920 × 1080p, 1280 × 720p Sub stream: 1280 × 720p, 640 × 480p FOV Horizontal:129°,Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Resolution Sub stream: 1280 × 720p, 640 x 480p FOV Horizontal:129°,Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
FOV Horizontal:129°,Vertical: 75° Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Wide dynamic range (WDR) Support 120 dB Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Supplement light IR light, up to 2.5 m Video compression standard H.264 Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Video compression standard Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Audio parameters Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Audio input 1 built-in omnidirectional microphone Audio compression standard G722.1、OPUS、G711U、G711A、G726 、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Audio compression standard G722.1、OPUS、G711U、G711A、G726 、AAC_LC、AAC_LD Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Audio output 1 built-in loudspeaker Audio compression bitrate 16/32/64 Kps	
Audio compression bitrate 16/32/64 Kps	
Audio quality Noise suppression and echo cancellation	
Volume adjustment Adjustable	
Capacity	
User capacity 2000	
Face capacity /	
Card capacity 10000	
Network parameters	
Network protocol TCP/IP, RSTP	
Wi-Fi /	
Bluetooth /	
3G/4G /	
Device interfaces	
Alarm input 4	
Network interface 1 RJ-45, 10/100 Mbps self-adaptive	
TAMPER 1	
Exit button 0	
RS-485 1	
USB /	
Wiegand /	
TF card 1(Reserved)	




Alarm output	1
Lock control	1 relay, Max. 30 VDC 2 A
Door contact input	1
Audio output	1 external loudspeaker(Reserved)
General	
Button	1 physical button
Installation	Surface mounting, Flush mounting
Indicator	2
Weight	Net weight: 0.190 kg Gross weight: 0.414 kg
Protective level	IP65
Working temperature	-40 °C to 53 °C (-40 °F to 127.4 °F)
Working humidity	10% to 95% (no-condensing)
Dimension (W × H × D)	181.6 mm × 103.6 mm × 29.5 mm (7.1" × 4.0" × 1.1")
Battery	/
Application environment	Outdoor
Power consumption	< 10 W
Language	English, Arabic, French (Europe), Russian, Spanish (Europe), Italian, German, Polish, Turkish, Portuguese, Portuguese (Brazil), Uzbek, Kazakh, Czech, Hungarian, Dutch, Romanian, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Lithuanian, Estonian, Latvian, Norwegian, Danish, Slovenian, Slovak, Hebrew, Swedish, Finnish, Mongolian, Vietnamese, Traditional Chinese

Available Model

DS-KV6133-ME1

Dimension





Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision Corporate Channel



6 hikvisionhq